

The StarBoard T-17SXLG and T-19WX
Interactive Panels

For lessons and presentations with real impact

Control a lesson or presentation from a podium or desk and project onto a large screen.



The StarBoard T-17SXLG and T-19WX panels are compact, interactive SXGA (T-17SXLG) and WXGA+ (T-19WX) resolution LCD displays that enable teachers to interact with teaching material in the classroom or lecture theatre. The panels are also ideal for one-to-one sessions with a student.

All StarBoard T-17SXLG and T-19WX panels are equipped with the StarBoard suite - intuitive interactive software that is all captured in an easy-to-master customisable toolbar.

Key features:

- LCD display screen.
- SXGA (T-17SXLG) and WXGA+ (T-19WX) resolution with excellent colour and contrast.
- Available in two aspect ratios, 4:3 (T-17SXLG) or 16:10 (T-19WX).
- StarBoard Suite of interactive software.
- Thin screen that assures natural, accurate operation.
- Eight hardware function buttons.
- Smoothly adjustable tilt stand.
- Ability for simultaneous viewing and annotation by multiple systems.
- VGA output connectors, providing an easy method of connecting projectors and monitors.

Available in two aspect ratios, 4:3 or 16:10

HITACHI
Inspire the Next

StarBoard T-17SXLG and T-19WX Interactive Panels for higher resolution

Technical Specifications	T-17SXLG	T-19WX
Display characteristics		
Driver type:	Active-Matrix Liquid Crystal Display (TFT)	
Effective screen size:	17 inches 337.920 mm (W) x 270.336 mm (H)	19 inches 408.24 mm (W) x 255.15 mm (H)
Resolution:	1,280 x 1,024 (SXGA)	1,440 x 900 (WXGA+)
Standard colours 1:	16.2 M colours	16.7 M colours
Brightness:	260 cd/m ²	300 cd/m ²
Contrast ratio:	450:1	1000:1
Viewing angles:	right 70°, left 70°, up 70°, down 70°	right 80°, left 80°, up 85°, down 85°
Digitiser characteristics		
Input system:	Electromagnetic induction	
Pen:	Stylus pen (Uses one AAA alkaline dry cell)*	
Coordinate resolution:	0.05 mm	0.025 mm
Reading accuracy:	+/- 0.5 mm	
Tracking speed:	Approx. 125 points per second	Approx. 130 points per second
Interface	USB interface: USB1.1	
Input/output		
Input:	Dsub 15-pin (analogue RGB) Stereo mini-jack (stereo audio)	
Output:	Dsub 15-pin (analogue RGB)	
Speaker output:	Stereo (1 W+1 W build-in amplifier)	Stereo (2.5 W+2.5 W, 4ohm, build-in amplifier)
System environment		
Temperature during use:	+10 – +35°C	+10 – +35°C
Temperature in storage:	-10 – +60°C	-20 – +60°C
Humidity during use:	30 – 80% (no condensation)	
Humidity in storage:	10 – 80% (no condensation)	
Dimensions		
External dimensions:	395.0 (W) x 375.0 (H) x 57.0 (D) mm (without stand)	462.0 (W) x 348.4 (H) x 60.0 (D) mm (without stand)
Weight:	Approx. 5.0 kg	Approx. 5.5 kg
Stand adjustment in the range of:	20° to 70°	10° to 75°
Power consumption / power supply		
Consumption:	40 W or less (4W or less in power saving mode)	50 W or less (2W or less in power saving mode)
Input (AC adapter):	AC 100 – 240 V, .50/60 Hz 1.0 A	AC 100 – 240 V, .50/60 Hz 1.2 A
Output:	DC 12 V, 3.3 A	N/A
Minimum system requirements		
CPU:	Pentium II 300MHz or faster	
Free hard drive space:	300MB or more	300MB or more
RAM:	128MB or more (256MB or more recommended)	
Display colours:	High Colour (16bit) or more	
Operating system (OS):	Windows 2000/XP	Windows 2000/XP/Vista
Software required:	Internet Explorer 6.0 or more, PowerPoint 2000/2002/2003/2007, DirectX 9.0c (when using Windows 2000/XP) Vista compatibility varies between product versions	Internet Explorer 6.0 or more, PowerPoint 2000/2002/2003/2007, DirectX 9.0c (when using Windows 2000/XP/Vista)
Other:	Video card that includes hardware overlay (when using video function) Pentium 4 1.8GHz or more and RAM 512MB or more are required for movie or network feature	

Please read safety instructions before using this product.

* Battery life: approximately 1800 hours. Battery life varies depending on the temperature and humidity of the usage environment.

Further information:



Functionality at the touch of a button



Hitachi Software Engineering (UK) Limited
Interactive Media Solutions Division
Hillgate House, 26 Old Bailey,
London EC4M 7HW, United Kingdom
Tel: +44 (0)207 246 6868
Fax: +44 (0)207 246 6860
Email: sales@hitachi-software.co.uk

Hitachi Software Engineering France S.A.S
Interactive Media Solutions Division
7th Floor,
64 rue du Dessous des Berges,
75013 Paris, France
Tel: +33 (0)153 827 600
Fax: +33 (0)153 827 619
Email: starboard@hitachisoft-eu.com

Hitachi Software Engineering Europe AG
Interactive Media Solutions Division
Kurfürstendamm 22,
D-10719 Berlin, Germany
Tel: +49 (0)30 8877 2600
Fax: +49 (0)30 8877 2610
Email: starboard@hitachisoft.de

www.hitachisoft-eu.com

HITACHI
Inspire the Next